

SHARK-TEX

Woven Fabric Digital Printer

Digital printing for home and vehicle textile, AD & SIGN
and outdoor banner



1/ Constant Traction Stepping System STRATOJET's Patented Technology

When a constant traction stepping system is used, the fabric can be in the floating state with good flatness when being printed. The traction is adjustable, which substantially broadens the fabric adaptability.

2/ Post-Printing Online Drying System STRATOJET's Patented Technology

The fabric will enter into the drying process immediately after printing procedure to avoid the sticky dirt generated on the fabric when entering into a twitch roller. The drying temperature and wind force could be adjusted to ensure the adaptability of a fabric which is thin or thick.

3/ Real-Time Waste Ink Collection System

The excessive ink droplets passing through the fabric upon printing would be uniformly collected by the waste ink tank and it is only required to clean the waste ink tank regularly to avoid drainage of waste water. The system can easily handle ultra-thin fabrics.

4/ Real-Time Drying & Heating System

Its two-sided-heating and fully-closed design can meet the requirements of sublimation with full color development, and when it is also used as the drying unit, the energy efficiency can be improved and the electricity consumption can be reduced.

5/ Professional Printing RIP Software

It supports the hyperfine screening technology conducting multi-channel color separating with a unique function of multiple duplicating, which can fully respond to the requirements of various patterns by the digital printing.

Specifications:

Printing technology	Model	SHARK-TEX	
	Nozzle	The Fifth Generation Micro Piezo Inkjet Printhead (DX5)	
	Quantity of nozzles	180 Nozzles X 8 rows X 2 units (2880 Nozzles)	
	Printing accuracy (maximum)	1440dpi	
	Ink dot size	Minimum 3.5 pl, maximum 21 pl	
	Color	Dual four colors	
	Printing accuracy / speed	360X1080dpi	57m ² /hr
		720X720dpi	35m ² /hr
720X1080dpi		28m ² /hr	
Printing width	3200mm		
Printing media	Width	The maximum material width is 3300 mm	
	Thickness	Depending on the material requirements	
	Type	Cotton, linen, silk, wool, polyester and blends, polyamide, acrylic, artificial cotton etc.	
	Maximum reel diameter	350mm	
	Maximum material weight	120kg	
Ink-supply system	Ink	Reactive ink, Disperse ink, Acid ink	
	Ink-supply mode	Continuous ink supply system(CISS)	
	Ink cartridge capacity	2000ml	
	Ink color	C, M, Y, K	
Heating system		Sublimation Heater	
Interface and power	Interface	High-speed USB 2.0 interface	
	Power source	Printer: Single phase 230V±10% 50/60Hz (110V is optional) Sublimation Heater: Three-phase 380V	
	Power	Printer: 2.5KW; Sublimation Heater: 7.8KW; Smoke filter: 0.75KW	
System software	RIP software	PHOTOPRINT(Textile Version), ONYX(Textile Version)	
	Control software	PrintManager	
	Control system	Windows XP / Windows 7 / Windows 8	
Operating environment	Temperature	15 C ~ 30 C	
	Humidity	40% ~ 80%	
Machine size	Printer: 4370mm (L)*1300mm (W) *1540mm (H);		
Machine net weight	Printer: 442kg; Sublimation Heater: 500kg; Smoke filter: 180kg;		

★ STRATOJET Special Textile Printing inks:

The high quality active, disperse, acid ink developed for STRATOJET digital textile printer is made from imported high-performance dyes free from heavy metals and other toxic substances but with pure color tones and high dye rate, and their fastness indicators are qualified in the tests conducted by professional agencies (the test reports from national authorities are available).

Convenience and Efficiency of Non-Belt Type

Constant traction stepping system is the highlight of the entire system. The broadening of fabric adaptability improves the integration level of program and reduces customer's investment costs and risks. Such expensive conductive-type inkjet printing machine is replaced by SHARK-TEX, resulting in very good effect. and make many fabrics avoid from the complex operation of traditional Self-adhesive Belt Transmission Printer. SHARK-TEX will not produce wastewater such as that is caused by conduction belt cleaning on traditional Self-adhesive Belt Transmission Printer, with smaller footprint and lower energy consumption. It truly embodies the characteristics of high efficiency, low energy consumption and modest prices of digital printing, which presents high investment value for customers engaged in fabric printing, exhibition, home decoration and advertising banners etc.

Perfect Combination of Quality and Speed

EPSON DX5 printhead is used, with the output resolution of up to 1440dpi and the printing speed of up to 55 m²/h, supporting variable-sized droplet technology.

Solid and Stable Body Structure Design

The bottom beam with fully wrapped slurry and steel back wall allows the printer to obtain solid horizontal support. The finished main aluminum alloy beam with high strength ensures the durability of the equipment and super-high printing resolution and the equipped Japanese THK linear mute guide rails, assures stable and high-speed movement of the printhead and in low noise level.

Meticulous Caring

A high-power DC servo motor cooperating with high-resolution raster and fully-closed positioning ensures the precision of the droplet printing position. A safe and reliable passive lifting cleaning mechanism uses a peristaltic ink pump to greatly extend the service life of the printhead. The distance between the printhead to the fabric could be manually adjusted depending on the fabric and the adjustable distance is 0-5mm.

For more information:

India/Asia/Pacific

Strategic Printing Solution Pvt. Ltd.
71/2 B1 Shivaji Marg
New Delhi-110015
Phone: +91 11 45410145
Phone: +91 11 45507946
Fax : +91 11 45054505
Email: info@stratojetprintingsolution.com

Europe/Middle East/Africa

Strategic Printing Solution Pvt. Ltd.
Unit 5 Adrienne Business Centre
Adrienne Ave, Southall
Middlesex UB1 2FJ, London
Phone: +447985116150
Email: info@stratojetusa.com

North / South America

Strategic Printing Solution Inc.
12110 E Slauson Ave #9
Santa Fe Springs, CA 90670
Phone: +16124240017
Fax: +15106572922
Email: info@stratojetusa.com

● STRATOJET reserves the right to revise the above-mentioned specifications, designs, sizes, materials or accessories due to the technical improvement, which will be subject to change without notice. ● The company name and product names stated in this brochure are trademarks or registered trademarks of the Company. ● Please make sure to regularly maintain the equipment for the better output quality in the actual output.

STRATOJET
HIGH PERFORMANCE | LARGE FORMAT | DIGITAL TECHNOLOGY

